

# Model: PFSWCPC50181081T10

## Features:

Submersible sewage pump designed for typical raw sewage and typical septic tank/effluent applications.

- **DISCHARGE:** 2" NPT Female, Vertical
- **LIQUID TEMPERATURE:** 32°-131°F
- **MOTOR HOUSING:** Cast Iron
- **IMPELLER:** Corrosion-resistant, reinforced Thermoplastic
- **PUMP BASE:** Cast Iron
- **SHAFT:** Stainless Steel
- **HARDWARE:** Stainless steel
- **GASKET:** Rubber
- **SEAL:** Lip, Rubber and Stainless Steel
- **UPPER BEARING:** Single row, ball, oil lubricated
- **LOWER BEARING:** Single row, ball, oil lubricated
- **POWER CORD:** 115V - SJTW, 18AWG/3C Cord with plug  
P/N: 10Ft. - PFL183062
- **MOTOR:** Energy efficient Permanent Split Capacitor (PSC), Oil filled, Class B insulation, Continuous duty (water depth must be at least 6" to prevent motor from overheating), Auto reset thermal overload protector, Circuit requirements; 115V - 15 AMPS
- **LEVEL CONTROL:** Wide Angle Tethered, Mechanical, Normally Open (N/O), Reinforced thermoplastic,  
115V - SJOW 18AWG/2C, 10 Ft. cord w/Piggy-back plug,  
On point - 15.1", Off point - 6.8"  
P/N: 10Ft. - PFTFS10D1810P1
- **WARRANTY:** 3 year



**Submersible Sewage Pump**  
**1/2HP, 115V**  
**2" Discharge,**  
**2" Spherical Solids**  
**Cast Iron**  
**Wide Angle Tethered Float**

MODEL	HP	Hz	Volts/Ph	RPM	FL AMPS	Cord Length	Wt.
PFSWCPC50181081T10	1/2	60	115/1	3450	7.4	10 ft	23.3 lbs



HEAD in Ft	0 Ft	5 Ft	10 Ft	15 Ft	Max Lift	Max Pressure
<b>FLOW Gallon/Minute</b>	108	83	70	40	18 Ft	7.9 psi
<b>FLOW Gallon/Hour</b>	6500	5000	4200	2400		

PF	TYPE U, SP, SW	Motor Housing P, C	Impeller Type P, C	Suction Plate Type P, C	Motor HP 25, 33, 50, 75, 1	30	50	Voltage 1 or 2	Float Switch Type M, F, T	Cord Length 10, 30
Power-Flo	U = Utility SP = Sump Pump SW = Sewage Pump	P = Plastic C = Cast Iron	P = Plastic C = Cast Iron	P = Plastic C = Cast Iron	25 = 1/4 HP 33 = 1/3 HP 50 = 1/2 HP 75 = 3/4 HP 1 = 1 HP	<b>Shut Off Head (ft)</b>	<b>Max Flow (Gal)</b>	1 = 115 V 2 = 230V	M = Manual F = Fixed Vertical T = Tethered	10 Ft 20 Ft

EXAMPLE: PFSWCPC3330501T10 - Power-Flo Pumps - Sump Pump - Cast Iron Motor Housing - Plastic Impeller - Cast Iron Suction Plate - 1/3HP - 30' Shut Off Head - 50 GPM Max Flow - 115 Volt - Tethered Float - 10' Cord



**Power-Flo Pumps & Systems**

a Power-Flo Technologies company



**WARNING:**  
 CANCER AND REPRODUCTIVE HARM-  
 WWW.P65WARNINGS.CA.GOV

Page  
43

877-24PUMPS • [www.powerflopumps.com](http://www.powerflopumps.com) or [sales@powerflopumps.com](mailto:sales@powerflopumps.com)

Model: PFSWCPC50181081T10

